



Boss™ LPS Low Pressure Systems

One-Piece Flange Adapters

Application:

- used in the transfer of water, brine, water-based chemicals, water-based acids, and gelatinous proppant (sand) slurry used at hydraulic fracturing sites

Sizes:

- 4"

Materials:

- adapter: iron
- nuts: forged steel
- O-ring (included with males): Buna-N

Features:

- flange x female or male hammer union straights (standard or short length)
- 45° elbows in female and male (flange x hammer union)
- two-piece nut is pinned and bolted for perfect alignment
- no welds or pipe threads to deteriorate causing premature leakage
- flange x male hammer union and flange x male elbow includes nut, bolts and O-ring

Specifications:

- all 4" Figure 206 threads are interchangeable with other reliable brands
- all 4" 150# flanges are compatible with other reliable brands

Approvals:

- adapter meets ASTM standards
- nuts meet AISI standards

3", 4", 6" and 8" one-piece frac fittings are also available.
Contact Dixon 877.963.4966 or visit dixonvalve.com



Dixon®

800 High Street • Chestertown, MD 21620
ph: 877.963.4966 • fx: 410-778-4702 • 800-283-4966
dixonvalve.com



© 2017 DVCC

Printed in the USA

BLPSOPFLANGE_0917_inhouse