

Venting EZ Boss-Lock

Application

· Transfer of fluids and solids, with a safe disconnection

Sizes

• 2", 3", and 4"

Features

- EZLink[®] tabs utilized as secondary locking mechanism to capture adapter in case of accidental uncoupling under pressure
- · Designed vent paths to help control direction of venting media
- EZ Boss-Lock cam arms for additional level of safety
- · Works with all standard cam and groove adapters

Materials

- 316 stainless steel
- 356T6 aluminum

Type C Coupler Coupler x Hose Shank

Size	Aluminum Part #	316 Stainless Steel Part #
2"	ALCEZ2001	RLCEZ2001
3"	ALCEZ3001	RLCEZ3001
4"	ALCEZ4001	RLCEZ400 ¹

¹ Hose drop shank

Type B Coupler Coupler x Male NPT

Size	Aluminum Part #	316 Stainless Steel Part #
2"	ALBEZ200	RLBEZ200
3"	ALBEZ300	RLBEZ300
4"	ALBEZ400	RLBEZ400

ALBEZ300

RLCEZ200

Dixon Specialty Products

225 Talbot Blvd. Chestertown, MD 21620 ph: 888.226.4673 fx: 410.778.1958 dixonvalve.com



Venting EZ Boss-Lock

Type D Coupler Coupler x Female NPT



Size	Aluminum Part #	316 Stainless Steel Part #
2"	ALDEZ200	RLDEZ200
3"	ALDEZ300	RLDEZ300
4"	ALDEZ400	RLDEZ400



Size	Aluminum Part #	316 Stainless Steel Part #
2"	ALHEZ200	RLHEZ200
3"	ALHEZ300	RLHEZ300
4"	ALHEZ400	RLHEZ400

© 2025 DVCC • VENTINGEZBOSS_0525